



## KAWASAKI ER6 / VERSYS 650 LINK PIPE



1.

### **Packing List:**

**1X LINK PIPE PR2250**  
**1X CARBON GASKET 48.5x42.5MM PR1884**  
**1X CLAMP 48x51MM PR2064**  
**1X SILENCER OF CHOICE AND STRAP**  
**1X CLAMP 52x55MM PR2065**  
**1X SILENCER MOUNTING BRACKET**  
**2X M8x35MM CAP SCREWS**  
**1X M8x20MM CAP SCREW**  
**3X M8 NYLOC NUTS**  
**6X M8 FLAT WASHERS**

### **Fitting Instructions**

*We strongly advise that this product is fitted by a qualified motorcycle mechanic.*

*Please check packing list before you start.*

*Always fit new gaskets.*

*Secure motorcycle on level ground using paddock stand. Recommended!*

*Remove exhaust silencer.*

2.

*Clean collector pipe of old gasket material, dirt and carbon deposits.  
Insert new carbon gasket inside slotted end of link pipe.  
Fit correct Clamp and insert it on to collector.*



*Fit bracket on to frame using cap screws, nuts and washers*



**3.**

*Fit silencer to link pipe, attach strap around silencer and to frame bracket.*



*Fully tighten all clamps and fasteners.  
Start engine and check for leaks.  
After your first ride out, check all fasteners for tightness.*