

YAMAHA XVS650 DRAGSTAR



- PACKING LIST:
- 2X DOWNPIPES
- 1X CAST FLANGE ADAPTOR
- 2X CYLINDER PORT GASKETS
- 3X CLAMPS
- 2X SILENCERS
- 2X MOUNTING BRACKETS
- 2X SPACERS
- 2X BOLTS AND WASHERS
- 1X TUBE OF SILICON SEALANT

• Fitting Instructions

- We advise that this product is fitted by an experienced motorcycle mechanic.
- Please check packing list before you start.
- Secure motorcycle on level ground using a paddock stand. Recommended!
- Remove standard exhaust system.
- Clean the cylinder ports of old gasket material, dirt and carbon deposits.
- Insert new gaskets.
- Fit the cast adaptor to the front cylinder head.
- Fit the downpipes to the cylinders finger tight at this stage.
- Assemble the front silencer bracket to the silencer.



• Fit the front, lower silencer to the downpipe fitting the mounting bracket with the spacer to the frame.



• Fit the rear, upper silencer bracket and spacer to the frame.





• Fit the rear, upper silencer to the downpipe and to the bracket.

- Starting from the front, working rearwards tighten all clamps and fasteners, checking alignment as you go.
- Start the engine and check for leaks.
- After your first ride out, check all fasteners for tightness.